

GEL COAT NOIR PARAFFINE ACCELERE - RP140977



SAFETY DATA SHEET
(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : GEL COAT NOIR PARAFFINE ACCELERE
Product code : RP140977.
UFI : P231-80GT-K00Q-S4HK

1.2. Relevant identified uses of the substance or mixture and uses advised against

N/A

1.3. Details of the supplier of the safety data sheet

Registered company name : SOROMAP PEINTURES VERNIS.
Address : 3, RUE MAURICE MALLET Z.A. DE BELIGON.17300.ROCHEFORT SUR MER.FRANCE.
Telephone : 05.46.88.36.10. Fax : 05.46.88.36.15.
contact@soromap.com
www.soromap.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).
Acute inhalation toxicity, Category 4 (Acute Tox. 4, H332).
Skin irritation, Category 2 (Skin Irrit. 2, H315).
Eye irritation, Category 2 (Eye Irrit. 2, H319).
May produce an allergic reaction (EUH208).
Reproductive toxicity, Category 2 (Repr. 2, H361).
Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).
Specific target organ toxicity (repeated exposure), Category 1 (STOT RE 1, H372).
Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS08



GHS02



GHS07

Signal Word :

DANGER

Product identifiers :

EC 202-851-5 STYRENE

Additional labeling :

EUH208 Contains OCTABENZONE. May produce an allergic reaction.

GEL COAT NOIR PARAFFINE ACCELERE - RP140977

EUH208 Contains HEXANOIC ACID, 2-ETHYL-, COBALT(2+) SALT. May produce an allergic reaction.

Hazard statements :

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H361 Suspected of damaging fertility or the unborn child .
 H372 Causes damage to organs through prolonged or repeated exposure (sense of hearing).
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/ ...

Precautionary statements - Response :

P302 + P352 IF ON SKIN: Wash with plenty of water/...
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statements - Disposal :

P501 Dispose of contents/container by approved organization

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 59 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	Classification (EC) 1272/2008	Note	%
CAS: 100-42-5 EC: 202-851-5 REACH: 01-2119457861-32 STYRENE	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 Repr. 2, H361 STOT RE 1, H372 Aquatic Chronic 3, H412	[i] [ii]	25 \leq x % < 50
CAS: 21645-51-2 EC: 244-492-7 ALUMINUM HYDROXIDE	GHS08 Wng STOT RE 2, H373	[i]	10 \leq x % < 25
CAS: 13463-67-7 EC: 236-675-5 REACH: 01-2119489379-17-0014 TITANIUM DIOXIDE		[i]	10 \leq x % < 25

GEL COAT NOIR PARAFFINE ACCELERE - RP140977

CAS: 7631-86-9 EC: 231-545-4 REACH: 01-2119379499-16 SILICON DIOXIDE		[i]	2.5 <= x % < 10
CAS: 1843-05-6 EC: 217-421-2 REACH: 01-2119557833-30 OCTABENZONE	GHS07 Wng Skin Sens. 1, H317		0 <= x % < 1
CAS: 136-52-7 EC: 205-250-6 REACH: 01-2119524678-29 HEXANOIC ACID, 2-ETHYL-, COBALT(2+) SALT	GHS08, GHS07, GHS09 Dgr Skin Sens. 1, H317 Eye Irrit. 2, H319 Repr. 1A, H360Fd Aquatic Chronic 3, H412 Aquatic Acute 1, H400 M Acute = 1	[ii]	0 <= x % < 1
CAS: 77-99-6 TRIMETHYLOPROPANE	GHS08 Wng Repr. 2, H361fd	[ii]	0 <= x % < 1

Specific concentration limits:

Identification	Specific concentration limits	ATE
CAS: 100-42-5 EC: 202-851-5 REACH: 01-2119457861-32 STYRENE		inhalation: ATE = 15 mg/l 4h (vapours)
CAS: 7631-86-9 EC: 231-545-4 REACH: 01-2119379499-16 SILICON DIOXIDE		inhalation: ATE = 5.01 mg/l 4h (dust/mist) oral: ATE = 3160 mg/kg BW
CAS: 136-52-7 EC: 205-250-6 REACH: 01-2119524678-29 HEXANOIC ACID, 2-ETHYL-, COBALT(2+) SALT		oral: ATE = 3129 mg/kg BW

Information on ingredients :

(Full text of H-phrases: see section 16)

[i] Substance for which maximum workplace exposure limits are available.

[ii] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures**In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Do not proceed with mouth-to-mouth or mouth-to-nose resuscitation. Use the appropriate equipment.

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

GEL COAT NOIR PARAFFINE ACCELERE - RP140977**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

GEL COAT NOIR PARAFFINE ACCELERE - RP140977

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Avoid exposure to pregnant women and warn women of child-bearing age of the possible risks

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of non-conductive

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Avoid exposure - obtain special instructions before use.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

GEL COAT NOIR PARAFFINE ACCELERE - RP140977**Storage**

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME :	VME :	Excess	Notes
100-42-5		20 ppm 86 mg/m ³		2(II)
7631-86-9		4E mg/m ³		

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m ³ :	VLE-ppm :	VLE-mg/m ³ :	Notes :	TMP No :
100-42-5	23.3	100	46.6	200	VLRC	84
13463-67-7		10				

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
100-42-5	100 ppm 430 mg/m ³	250 ppm 1080 mg/m ³			
21645-51-2	10 mg/m ³	-	-	-	TI
13463-67-7	4 mg/m ³				

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

GEL COAT NOIR PARAFFINE ACCELERE - RP140977

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

- A3 (Brown)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****Physical state**

Physical state : Viscous liquid.

Colour

colour : N/A

Odour

Odour threshold : 0.1 ppm (valeur du styrène)

Melting point

Melting point/melting range : Not specified.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not specified.

Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) Not stated.

:

Explosive properties, upper explosivity limit (%) Not stated.

:

Flash point

Flash Point : 31.00 °C.

Auto-ignition temperature

Self-ignition temperature : 490 °C.

Decomposition temperature

Decomposition point/decomposition range : Not specified.

GEL COAT NOIR PARAFFINE ACCELERE - RP140977**pH**

pH : Not relevant.
pH (aqueous solution) : Not stated.

Kinematic viscosity

Viscosity : 35000 - 420000 mPa.s

Solubility

Water solubility : Insoluble.
Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density and/or relative density

Density : 1.18 - 1.24

Relative vapour density

Vapour density : Not stated.

Particle characteristics

The mixture does not contain nanoforms.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

GEL COAT NOIR PARAFFINE ACCELERE - RP140977

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Harmful by inhalation.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

Suspected human reproductive toxicant.

Causes severe damage to organs in the event of repeated or prolonged exposure.

11.1.1. Substances

Acute toxicity :

HEXANOIC ACID, 2-ETHYL-, COBALT(2+) SALT (CAS: 136-52-7)

Oral route : LD50 = 3129 mg/kg bodyweight/day
Species : Rat
OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

Dermal route : LD50 > 2000 mg/kg bodyweight/day
Species : Rat
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Dusts/mist) : LC50 > 2000 mg/l

OCTABENZONE (CAS: 1843-05-6)

Oral route : LD50 > 10000 mg/kg bodyweight/day
Species : Rat
OECD Guideline 423 (Acute Oral toxicity Acute Toxic Class Method)

Dermal route : LD50 > 10000 mg/kg bodyweight/day
Species : Rabbit
OECD Guideline 402 (Acute Dermal Toxicity)

SILICON DIOXIDE (CAS: 7631-86-9)

Oral route : LD50 = 3160 mg/kg bodyweight/day
Species : Rat

Dermal route : LD50 > 5000 mg/kg bodyweight/day
Species : Rabbit

Inhalation route (Dusts/mist) : LC50 = 5.01 mg/l
Duration of exposure : 4 h

TITANIUM DIOXIDE (CAS: 13463-67-7)

Oral route : LD50 > 5000 mg/kg bodyweight/day
Species : Rat
OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

GEL COAT NOIR PARAFFINE ACCELERE - RP140977

Dermal route :	LD50 > 5000 mg/kg bodyweight/day Species : Rabbit
Inhalation route (Dusts/mist) :	LC50 > 6.8 mg/l Species : Rat
STYRENE (CAS: 100-42-5) Oral route :	LD50 > 5000 mg/kg bodyweight/day Species : Rat
Dermal route :	LD50 > 5000 mg/kg bodyweight/day Species : Rat
Inhalation route (Vapours) :	LC50 = 15 mg/l Species : Rat Duration of exposure : 4 h
Skin corrosion/skin irritation : TITANIUM DIOXIDE (CAS: 13463-67-7)	Species : Rabbit OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Respiratory or skin sensitisation : TITANIUM DIOXIDE (CAS: 13463-67-7) Local lymph node stimulation test :	Non-Sensitiser. Species : Mouse OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Guinea Pig Maximisation Test (GMPT) :	Non-sensitiser. Species : Guinea pig OECD Guideline 406 (Skin Sensitisation)
Germ cell mutagenicity : TITANIUM DIOXIDE (CAS: 13463-67-7)	No mutagenic effect.
Mutagenesis (in vivo) :	Negative. Species : Mouse OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Mutagenesis (in vitro) :	Negative. Species : Mammalian Cell Line OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Ames test (in vitro) :	Negative. With or without metabolic activation.
Carcinogenicity : TITANIUM DIOXIDE (CAS: 13463-67-7) Carcinogenicity Test :	Negative. No carcinogenic effect.
Specific target organ systemic toxicity - repeated exposure : STYRENE (CAS: 100-42-5) Inhalation route :	C = 0.21 mg/litre/6h/day

GEL COAT NOIR PARAFFINE ACCELERE - RP140977

Duration of exposure : 90 days
OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

HEXANOIC ACID, 2-ETHYL-, COBALT(2+) SALT (CAS: 136-52-7)

Oral route :
C = 3 mg/kg bodyweight/day
Species : Rat
Duration of exposure : 90 days
OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Inhalation route :
C = 0.31 mg/litre/6h/day
Species : Rat
Duration of exposure : 90 days

11.1.2. Mixture**Acute toxicity :**

Inhalation route (Dusts/mist) : Harmful by inhalation.
Duration of exposure : 4 h
LC50 = 4.923 mg/l

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

11.2. Information on other hazards**Endocrine disrupting properties**

The mixture does not contain any substance evaluated as an endocrine disruptor with effects on human health.

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 7631-86-9 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 13463-67-7 : IARC Group 2B : The agent is possibly carcinogenic to humans.

CAS 100-42-5 : IARC Group 2A : The agent is probably carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity**12.1.1. Substances**

OCTABENZONE (CAS: 1843-05-6)

Fish toxicity :
LC50 > 100 mg/l
Species : Danio rerio
Duration of exposure : 96 h

Crustacean toxicity :
EC50 > 0.0038 mg/l
Species : Daphnia magna
Duration of exposure : 48 h

Algae toxicity :
ECr50 > 100 mg/l
Species : Desmodesmus subspicatus
Duration of exposure : 72 h

HEXANOIC ACID, 2-ETHYL-, COBALT(2+) SALT (CAS: 136-52-7)

Fish toxicity :
LC50 = 22.32 mg/l
Duration of exposure : 96 h

Crustacean toxicity :
EC50 = 5.89 mg/l

GEL COAT NOIR PARAFFINE ACCELERE - RP140977

	Duration of exposure : 48 h
Algae toxicity :	ECr50 = 0.654 mg/l Duration of exposure : 72 h
SILICON DIOXIDE (CAS: 7631-86-9) Fish toxicity :	LC50 = 10000 mg/l Duration of exposure : 96 h
Crustacean toxicity :	EC50 > 5000 mg/l Duration of exposure : 48 h
Algae toxicity :	ECr50 > 173.1 mg/l Duration of exposure : 72 h
TITANIUM DIOXIDE (CAS: 13463-67-7) Fish toxicity :	LC50 > 10000 mg/l Species : <i>Cyprinodon variegatus</i> Duration of exposure : 96 h OECD Guideline 203 (Fish, Acute Toxicity Test)
Crustacean toxicity :	EC50 > 1000 mg/l Species : <i>Daphnia magna</i> Duration of exposure : 48 h OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Algae toxicity :	ECr50 > 100 mg/l Species : <i>Pseudokirchnerella subcapitata</i> Duration of exposure : 72 h OECD Guideline 201 (Alga, Growth Inhibition Test)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability**12.2.1. Substances**

HEXANOIC ACID, 2-ETHYL-, COBALT(2+) SALT (CAS: 136-52-7)

Biodegradability : Rapidly degradable.

OCTABENZENE (CAS: 1843-05-6)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

TITANIUM DIOXIDE (CAS: 13463-67-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

STYRENE (CAS: 100-42-5)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential**12.3.1. Substances**

TITANIUM DIOXIDE (CAS: 13463-67-7)

Bioaccumulation : BCF > 19

GEL COAT NOIR PARAFFINE ACCELERE - RP140977

Species : Oncorhynchus mykiss (Fish)

HEXANOIC ACID, 2-ETHYL-, COBALT(2+) SALT (CAS: 136-52-7)
Octanol/water partition coefficient : log K_{ow} = 2.96**12.4. Mobility in soil**

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with environmental effects.

12.7. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 2 : Hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2022 [41-22] - ICAO/IATA 2024 [65]).

14.1. UN number or ID number

1866

14.2. UN proper shipping name

UN1866=RESIN SOLUTION, flammable

14.3. Transport hazard class(es)

- Classification :



3

14.4. Packing group

III

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	30	5 L	-	E1	3	D/E

If Q <450l, see 2.2.3.1.5.1.

GEL COAT NOIR PARAFFINE ACCELERE - RP140977

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	3	-	III	5 L	F-E. S-E	223 955	E1	Category A	-

if Q < 450 l see IMDG 2.3.2.5.

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	III	355	60 L	366	220 L	A3	E1
	3	-	III	Y344	10 L	-	-	A3	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15 : REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/707.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2024/197. (ATP 21)

Container information:

The mixture is contained in packaging that does not exceed 125 ml.

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): <https://echa.europa.eu/substances-restricted-under-reach>.

Explosives precursors :

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

Particular provisions :

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBWs) :

WGK 2 : Hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360Fd	May damage fertility. Suspected of damaging the unborn child.

GEL COAT NOIR PARAFFINE ACCELERE - RP140977

H361	Suspected of damaging fertility or the unborn child .
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure .
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

CMR: Carcinogenic, mutagenic or reprotoxic.

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

VLRI : Indicative limit value

VLRC : Indicative constraint value

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.